



AAA12 Series

Compact 50W
Ku-Band SSPA

This small and lightweight SSPA is ideal for SOTM applications while also offering benefits for fixed and maritime applications.

Designed to be mounted on the feed horn, the SSPA has “Best in Class” efficiency and “lowest power consumption” with less than 330W. The unit works on a wide range DC power supply of 38V to 60V. Innovative and efficient thermal design makes this SSPA one of the smallest, robust, reliable and rugged enough to withstand outdoor conditions in the industry.

The unit can be configured to work in 1:1 redundant mode by adding on a simple redundancy option to the basic unit.

Features

- Compact and lightweight
- Feed mountable
- Available in both standard and extended Ku-Band
- Forward power detection facility
- Intuitive monitoring & control through RS232/485 & Ethernet (SNMP & HTTP)
- Auto ranging 38 to 60VDC Power Supply
- Optional input AC Voltage
- Automatic fault identification & alarm generation
- Wide operating temperature range -40°C to +60°C
- IP65 rated housing (Weather proof Construction)
- RoHS compliant

Quality Assurance

100% of all SSPAs go through stringent quality checks in addition to well defined Electrical Stress Screening to ensure operation in harsh outdoor environments. The SSPAs are also subjected to seal test for water ingress verification.

Reliability

Field proven under harsh environment conditions, Agilis ODU's can withstand temperature ranging from -40°C to +60°C with up to 100% humidity.

AAA12 Series

Compact 50W
Ku-Band SSPA



Technical Specifications

RF Specifications

Transmit Frequency	14.0GHz – 14.5GHz 13.75GHz – 14.5GHz
Output Power (P _{1dB})	47dBm
Spectral Re-growth	30dBc @ 2dB below rated power (P _{1dB}) at 1.0 x symbol rate offset for OQPSK or QPSK
Small Signal Gain	44dB Min
Gain Flatness	±0.75dB over the O/P frequency band
Gain Variation	±0.75dB over the operating temperature range
Gain Control	20 dB in step of 0.5 dB (optional 0.1dB step size)
O/P spurious	According to EN301428
Phase Noise @ Offset	
1KHz	-73dBc/Hz
10KHz	-83dBc/Hz
100KHz	-93dBc/Hz
I/P VSWR	1.5:1
O/P VSWR	1.25:1 (with optional external isolator)
Noise Power Density Tx BD	70dBW/4KHz
Rx BD	142dBW/4KHz

DC Power

Prime Power	48VDC (range 38 to 60VDC) via external MS connector Optional 230VAC (range 96 to 264 VAC)
Power Consumption	280W (Typical @ 46dBm)

Interfaces

IF Input Interface	50Ohms N-type Female
Output Interface	WR 75G

Monitor And Control

Monitor	SSPA temperature Status alarm RF output power LED status indication
Control	Attenuation RF output mute
Interface	RS232/485 & Ethernet (SNMP & HTTP) via external MS connector
Tx Redundancy	External RCU (optional for 1+1 redundancy system requirement)

Environmental

Operating Temperature	-40°C to +60°C
Humidity	Up to 100% Weather protection sealed to IP65

Mechanical

Dimensions	200L x 130W x 130H mm 200L x 130W x 235H mm (AC option)
Weight	3.7kg / 8.14lbs 6.0kg / 13.22lbs (AC option)
Colour	White Powder Coat

Compliance Standard

IEC 609501-2nd Edition	International Safety Standard for Information Technology Equipment
ETSI EN 301 489-12	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) Standard for radio equipment and services; Part 12: Specific conditions for Very Small Aperture Terminal, Satellite Interactive Earth Stations operated in the frequency ranges between 4GHz and 30GHz in the Fixed Satellite Service (FSS)
ETSI EN 301 489-1	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility Standard for Radio Equipment and Services
FCC Part 15 Class B	Two levels of radiation and conducted emissions Limits for unintentional radiators (FCC Mark)

Note: All specifications are subject to change without notice.
Rev. 010714

www.agilissatcom.com

For more information, please send enquiry to:

Singapore (Headquarters)

mktg_satcoms@stee.stengg.com

USA

usa_satcoms@stee.stengg.com

Europe

europe_satcoms@stee.stengg.com

