

HIGH POWER AMPLIFIERS 750 WATT

HPA 2713 SERIES FOR KU-BAND



HPA 2713 A (indoor)



HPA 2713 B (outdoor)

ND SatCom has been a supplier to the Satcom industry for over 25 years. All necessary features required in today's satellite communication applications such as serial/parallel M&C interfaces, local and remote panels are available in this HPA product line. All RF parameters can be monitored and controlled on the front panel. The modular construction ensures easy servicing. The high voltage section is potted and all other electrical components are coated to protect against humidity and dust.

The outdoor versions of this series are available with two choices of remote panel. The standard panel allows the user to control the operating status of the amplifiers (standby, run, RF-on). An optional microprocessor-controlled remote panel displays additional status information and gives extended control options.

// Unmatched TWT durability and reliability through our intelligent high-tech power supply unit //

Key Features

- / Unmatched RF performance
- / Enhanced TWT longevity
- / High-tech power supply unit for highly reliable operation
- / Indoor and outdoor versions
- / Integrated power factor correction
- / Low power consumption (max. 2350 W)
- / Light-weight (only 36 kg / 79 lbs)
- / Small dimensions
- / Low phase noise (typ. IESS 308/309)

Options

- / Integrated linearizer
- / Redundancy switching
- / Remote control panel (outdoor version)

TECHNICAL SPECIFICATION

HPA 2713 SERIES FOR KU-BAND

RF-SPECIFICATION

Frequency Range	13.75 - 14.50 GHz
Flange Power	> 630 W, > 58 dBm
TWT Power	750 W Tube
Gain at Rated Power	> 72 dB
Gain at 10 dB Backoff	> 76 dB
Gain Variation	< 1.0 dB / in any 80 MHz, < 2.5 dB / in any 500 MHz, < 5.5 dB / full band
Gain Slope	< 0.02 dB / MHz
Gain Stability	< ±0.25 dB / °C / 24 hrs after 30 min warm-up
Gain Adjust	> 0 - 20 dB, ±0.1 dB setability
Group Delay (in any 40 MHz)	< 0.01 ns / MHz linear, < 0.005 ns / MHz ² parabolic, < 0.5 ns ripple
Intermodulation	< -21 dBc at 6 dB below rated power without linearizer < -30 dBc at 4 dB below rated power with linearizer
Noise Figure	< 15 dB max.
AM/PM Conversion	< 2.5° / dB at 7 dB below rated power, < 6° / dB at rated output power
Harmonic Output Suppression	< -80 dBc at rated output
Noise and Spurious Emissions	< -65 dBW / 4 kHz (inband) < -120 dBW / 4 kHz 10.7..12.7 GHz < -115 dBW / 4 kHz 18.0..19.0 GHz
Phase Noise	Meets IESS 308/309
VSWR	1.3:1 Input, 1.2:1 Output (waveguide)

MECHANICAL SPECIFICATION

	Version A (indoor)	Version B (outdoor)
RF Connectors		
Inputs	SMA (input) / N-Jack (testport)	N-Jack (input/testport)
Outputs	WR 75 Waveguide Output, grooved, threaded M4 or UNC 6/32	WR 75 Waveguide Output, grooved, threaded UNC 6/32
Serial Remote Interface	9-pin D fem. RS422/RS485 (optional R232)	PT 851-00R12-10S50 RS422/RS485
Alarm / Mute Interface	15-pin D fem.	PT 851-00R12-10S50
Parallel Remote Interface	25-pin D fem.	PT 851-00R19-10S50
Main Power Inlet	AMP C 16-1 4 pol. P	AMP C 16-1 4 pol. P
Dimension	483 x 133 x 650 mm (3 RU)	294 x 233 x 649 mm
Weight	< 36 kg / 79 lbs	< 36 kg / 79 lbs
Cooling	forced air min. 200 m ³ /h	forced air min. 200 m ³ /h
Noise Level (cooling fan)	< 65 dBA measured in 1 m distance	< 65 dBA measured in 1 m distance

ELECTRICAL SPECIFICATION

Prime Power	190 to 240 VAC / 50-60 Hz, single phase
Power Consumption	< 2350 W max.
CE Directive	73/23/EEC and 92/31/EEC 89/336/EEC 1999/5/EC

ENVIRONMENTAL SPECIFICATION

Operating Temperature Range	-10°C to +50°C	-40°C to +50°C
Operating Humidity	< 95% non-condensing at 40°C	< 95% condensing at 40°C
Shock and Vibration	for normal commercial transport	for normal commercial transport



ND SatCom AG
P.O. Box
88039 Friedrichshafen
Germany
Phone +49 7545 9390
Fax +49 7545 939 8780
info@ndsatcom.com
www.ndsatcom.com

AMERICAS
Phone +1 214 231 3400
Fax +1 214 231 3399
www.ndsatcom.com

MIDDLE EAST
Phone +971 2 443 6531
Fax +971 2 443 6650
www.ndsatcom.ae

CHINA
Phone +86 10 8479 5500
Fax +86 10 8456 4848
www.ndsatcom.com.cn

RUSSIA
Phone +7 495 995 3305
Fax +7 495 995 3307
www.ndsatcom.ru

INDIA
Phone +91 124 401 2612/15
Fax +91 124 404 4612
www.ndsatcom.co.in

TURKEY
Phone +90 216 373 7390
Fax +90 216 373 7396
www.ndsatcom.com.tr